



- Variable Speed 4D Joystick
- Supports IP & Serial Control Modes
- Multi Compatibility Built-in Pelco-P Pelco-D
- Ergonomic Design
- ONVIF Protocol & PoE Support

EVT-KBD-P

4D PoE PTZ CONTROL
KEYBOARD JOYSTICK

ONVIF®



EVT-KBD-P 4D PoE PTZ-CONTROL KEYBOARD JOYSTICK

General Specifications

Power	PoE – Via USB Interface
Compliance	ONVIF
Approvals	EN 55032 Class B, EN 55024, EN 61000-6-2, FCC Part 15 Subpart B Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B, VCCI Class B, EN/IEC/UL 62368-1, KC KN-32 Class B KN 35, EN 60529 IP20
Working Temp.	-10°C~55°C / 14°F~131°F
Work humidity	20%~80% frostless
Size	179.2mm x 321mm x 105.7mm 7 inch x 12.64 inch x 4.2 inch
Weight	1.63kg/3.6pound

Material	Full Metal
Screen	TFT LCD 320*240
Warranty	3-Years
System requirements	Windows 10, Windows 7, Windows XP, Windows Vista, Windows 12 (Server), Windows 8 (Server), USB 2.0 port
Functionality	One Key Switch-Thanks to the 7 buttons design, the E2 joystick support 7 buttons one key switch from CAM1 to CAM7 for fast and easy switch.No need to input camera address and select anymore.

All rights reserved. Appearance and specifications are subject to change without prior notice

