



- High Quality Imaging with 8MP Resolution
- 1 /2.8" Sony Starvis Back-Illuminated CMOS Sensor
- Support H.264/ H.264+/H.265/ H.265+/JPEG/AVI/MPEG
- 2.7-13.5mm Motor Zoom
- Support Warm Light LED 4000K Up to 25m
- 140dB WDR, Pro-Series, IP67, IK10 Metal Housing



Human/Vehicle
Detection



Intelligent
Analysis



True WDR



SD Card
slot



Audio In/out



IP67



Smart IR



Alarm In/out

EVT-P-82713-DIV

8MP SMART-IR DOME
NETWORK CAMERA

EVT-P-82713-DIV 8MP SMART-IR DOME NETWORK CAMERA

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS
Resolution	8MP
Effective Pixels	3864(H)*2192(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
Audio Compression	G711A/U, AAC
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimum Illumination	Color : 0.005 Lux @ (F1.0, AGC ON), 0 Lux with white light
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional

Lens

Focal Length & FOV	2.7-13.5mm Motor Zoom, horizontal FOV 108°—30°, vertical FOV 56°—17°, diag. FOV 130°—34°
Lens Type	Auto
Focus Control	Auto
Aperture	F1.6 - F3.3
Pixels	8MP

Night Vision

Infrared LED	No, Support Warm light LED 4000K, up to 25m
Infrared Distance	N/A
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode

Network

Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP, Qos, 802.1x
ONVIF	Support ONVIF 19.12(Profile S/T/G)
P2P	YES
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160@25fps, 3072*2048@25fps
Main Stream 2	2592*1536@25fps, 2560*1440@25fps
Main Stream 3	1920*1080@25fps, 1280*720@25fps
Sub Stream 1	1280*720@25fps, 720*480@25fps
Sub Stream 2	352*288@25fps

Sub Stream 3	N/A
Tri Stream	1280*720@25fps, 720*480@25fps, 352*288@25fps
IE Brower	IE8-11, Google Chrome, Firefox, Mac Safari
Smart Phone	iPhone, Android

AI Function

Intelligent Analysis

Face Detection, Intrusion Detection (based on human and Vehicle Detection), Line Cross Detection (based on human and Vehicle Detection), Loiter Detection, People Gather Detection (based on human detection), Motion detection based on human detection

Camera Features

Day/Night	Color
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, Anti Flicker, Video Tampering, HLC, Distortion
Full Color	Support
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	140dB
Motion Detection	Support (support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederland, Czech, Vietnamese

Interface

Audio	Optional 1 Built-in MIC
Alarm	Optional 1 Channel Input/Output
SD Card Slot	Optional Internal, Support Max 1TB, Built in 4G Storage
RS485	N/A

General

Housing	Metal, IP67, IK10
Anti-cut Bracket	No
IR Cut Filter	YES
Operation Temperature	-30°C ~ +60°C RH95% Max
Storage Temperature	-30°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	φ 126 x 108(H)mm
Weight	800g

All rights reserved. Appearance and specifications are subject to change without prior notice




ACCESSORIES



Outdoor Long Wall-Mount Bracket EVT-WM236-OL

- Material: Metal
- Color: White
- Size (mm): 245 (W) x 160(D) x 163(H)



Ceiling-Mount Bracket EVT-CM236

- Material: Plastic
- Color: White
- Size (mm): 116 (W) x 116(D) x 49.4(H)



Indoor Short Wall-Mount Bracket EVT-WM236-IS

- Material: Metal
- Color: White
- Size (mm): 173 (W) x 111 (D) x 114(H)



Junction Box EVT-JB236

- Material: Plastic
- Color: White
- Size (mm): 138.5 (L) x 137.4(W) x 65.5(H)



IK10

Impact
Rating



IP67

Ingress
Protection
Rating

Eagle Vision Technology Co.

938 N. 200th St., Suite B, Shoreline-Seattle
WA 98133, UNITED STATES
Tel: 1-800-204-4012
www.eaglevisiontech.com
sales@eaglevisiontech.com

Distributed By

