



- High Quality Imaging with 5MP Resolution
- 1 /2.8" Progressive Scan CMOS Sensor
- Up to 300m Video Transmission Distance
- 2.7-13.5mm Motorized Lens
- IR Distance Up to 30m
- IP66, Metal Housing

EVT-SDI-52713-DIV

5MP SMART-IR HD-SDI
ANALOG DOME CAMERA



Water-Proof
Rated



Smart IR



Varifocal



RoHS
COMPLIANT



FCC



CE

EVT-SDI-52713-DIV 5MP SMART-IR HD-SDI ANALOG DOME CAMERA

Imaging Device	1/2.8" Progressive CMOS
Scanning System	Progressive Scanning
Min. Illumination	0.05 lux @F1.2(AGC ON),0Lux with IR ON
Video Output	BNC
Resolution	5MP 2592 (H) ×1944 (V)
Max. Framerate	5AHD/5TVI: 5MP@20fps, 4AHD/4CVI/4TVI: P@25fps, N@30fps, CVBS: 960H
Max. Aperture Ratio	F1.8-3.3
Lens Type/ Focal Length	Motorized lens/2.7-13.5mm
Audio	N/A
Audio Range	N/A
IR Distance	30-35m
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	WDR (Off/On)
Digital Noise Reduction	3D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Video Transmission Distance	MAX 300M (Cable: 5C 2V)
Operating Temperature / Humidity	-30°C ~ 55°C / 90%
Ingress Protection	IP66
Input Voltage/Current	12V DC
Power Consumption	IR OFF ≤ 2W, IR ON ≤ 6.5W
Color / Material	Metal

All rights reserved. Appearance and specifications are subject to change without prior notice



DIMENSIONS

