



- High Bandwidth for Quality Imaging
- Display Resolution: 5MP-Lite: 20fps, 4MP-Lite: 30fps, 1080P/720P/960H: 30fps IP: 5MP/4MP/1080P/720P
- Playback: 5MP-lite: 240fps (Max 16CH playback)
- 2.7-13.5mm Motorized Lens
- Intelligence: Perimeter Intrusion Detection, Line Crossing, Human/Vehicle Detection, Face Detection/Recognition



## EVT-SDI-532-DVR

32-CH HD-SDI 4-SATA  
DIGITAL VIDEO RECORDER



# EVT-SDI-532-DVR 32-CHANNEL HD-SDI 4-SATA HDD DVR

## SCALE

|                     |                       |                                     |
|---------------------|-----------------------|-------------------------------------|
| Recording Bandwidth | Inputs                | 16Mbps                              |
|                     | out                   | 216Mbps                             |
|                     | Analog video-input    | 32CH inputs                         |
| Live                | IP Video Input        | 4CH                                 |
|                     | Composite Video Input | Max. 36CH (Analog video + IP video) |

## PERFORMANCE

|                        |                              |                                                                                                                                                                                   |
|------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recording and Playback | Compression                  | Audio: G.711a, Video: H.264/H.265                                                                                                                                                 |
|                        | Display resolution           | 5MP-Lite: 20fps, 4MP-Lite: 30fps, 1080P/720P/960H:30fps IP: 5MP/4MP/1080P/720P                                                                                                    |
|                        | Speed                        | Analog: 5MP-Lite: 15fps (Each CH), 4MP-Lite: 20fps (Each CH), 1080P: 15fps (Each CH), 720P: PAL: 25fps(Each CH)/NTSC: 30fps(Each CH) IP: PAL: 25fps(Each CH)/NTSC: 30fps(Each CH) |
|                        | Event                        | MD (Sensitivity Level 1~8); Video Loss; Beep, Email, Push Notification to Mobile APP                                                                                              |
|                        | Playback function            | Fast-Forward / backward (2x, 4x, 8x,16x); Slow-Forward (1/2x, 1/4x, 1/8x, 1/16x)                                                                                                  |
|                        | Playback                     | 5MP-lite: 240fps (Max 16CH playback )<br>4MP-lite: 320fps (Max 16CH playback)<br>1080P: 480fps (Max 16CH playback)<br>720P:960fps (Max 16CH playback)                             |
|                        | Artificial Intelligence (AI) | Perimeter Intrusion Detection, Line Crossing Detection, Human/Vehicle Detection, Face Detection, Face Recognition                                                                 |
| P/W Reset              |                              | YES                                                                                                                                                                               |
| Monitors               | BNC                          | 1 (704*576)                                                                                                                                                                       |
|                        | VGA                          | 1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)                                                                                                                             |
|                        | HDMI                         | 1(1024*768,1280*720,1280*1024,1440*900, 1920*1080,2560*1440(2K),3840*2160(4K))                                                                                                    |
| Input/Output           | Ethernet                     | 2 RJ45 100/1000 Base-T                                                                                                                                                            |
|                        | USB                          | USB2.0*1(front); USB3.0*1(rear)                                                                                                                                                   |
|                        | Audio                        | 8 in / 1 out                                                                                                                                                                      |
|                        | E-SATA                       | 1                                                                                                                                                                                 |
|                        | HDD                          | 4 SATA HDD, Up to 10TB                                                                                                                                                            |
|                        | RS485                        | 1                                                                                                                                                                                 |
|                        | Alarm Input/out              | 16 in /1 out                                                                                                                                                                      |

## GENERAL

|               |                                |                                         |
|---------------|--------------------------------|-----------------------------------------|
| Mechanical    | Dimension (WxDxH)              | 378*326*66mm                            |
| Electrical    | Input Voltage/Current          | DC12V/5A                                |
|               | Power Consumption "NO HDD"     | 21W                                     |
| Environmental | Operating Temperature/Humidity | Temperature: -10°C~+50°C (32°F ~ 104°F) |
|               |                                | Humidity: Less than 90%RH               |

## REAR-VIEW



All rights reserved. Appearance and specifications are subject to change without prior notice

