



- Steel Frame Front door with Certified Safety Glass
- IP20 Protection Class
- Swivel Handle with Profile Half-Cylinder Lock on Front Door
- 4x Leveling Feet
- 19" Galvanized and Numbered Profile Rails
- 1200kg Load Capacity

EVT-C-8842

STANDING 42U CABINET 800x800



EVT-C-8842 STANDING 42U CABINET 800x800

Features

- Steel rear door with round lock incl. two-part
- 1-point locking on the front door, 1-point locking on the rear door (incl. locking aid at the top and bottom)
- Removable side panels with type 333 sash lock and additional snap lock
- 483 mm (19") profile rails are connected to depth struts for increased stability
- Vertical cable ducts with cable routing aids and cover installed in the front panel
- Modular, openable base chassis with removable 19" blind panels (450 x 537 mm)
- Cable inlets in the base: 400 x 170 mm (rear), 90 x 550 mm (side)
- Cable inlets in the roof: 90 x 550 mm (lateral)
- Roof is prepared to accommodate a fan unit and an attached, removable cover
- Earthing points in the cabinet and on removable doors/walls
- Protection class IP20
- High load capacity of the 483 mm (19") profile rails of up to 1200 kg

Specifications

Standard size	Height units (U)	42U
	Width (mm)	800
	Depth (mm)	800
Shipping style	Shipping style	Mounted
Front door	Style (800 mm width cabinets)	Complete steel frame with safety glass, single opening
	Locking	Pivot lever with lock ready for profile-half cylinder (adapter included)
	Opening angle	270°
Rear door	Style (800 mm width cabinets)	Steel door, double opening
	Locking	Pivot lever with lock ready for profile-half cylinder (adapter included)
	Opening angle	270°
Side panels	Side panels	Detachable with snap-in latches, lockable
Fan area in roof	Fan area in roof	482.6 mm (19") blind panels for individual use
	Fan area cover	482.6 mm (19") blind panels for individual use
Vertical cable ducts		Installed in front (left & right)
Cable entry in base	Style (800 mm width cabinets)	482.6 mm (19") blind panels for individual use
	Style (800 mm width cabinets)	Additional cable entry brushes left & right
Cable entry in top	Style (800 mm width cabinets)	482.6 mm (19") blind panels for individual use
	Style (800 mm width cabinets)	Additional cable entry brushes left & right
Load capacity	19" rails	1200 kg

All rights reserved. Appearance and specifications are subject to change without prior notice

VIEWS & ACCESSORIES

